

Scanners

Wired / Handheld



| | | 1000 K/R/U | 1090+ | 1100 | 1200 |
|-------------------------|---|--|---|-----------------------------|----------------------------------|
| Performance | Category | CCD contact scanner | CCD contact scanner (for codes up to 90mm wide) | Linear imaging scanner | Laser scanner |
| | Optical sensor | 2048 pixels | 2048 pixels | 3648 pixels | Laser |
| | Light source | Red LED (660 nm) | Red LED (650 nm) | Red LED (630 nm) | Visible laser diode (650 ±15 nm) |
| | Resolution | 3 mil | 4 mil | 3 mil | 4 mil |
| | Depth of field <small>depends on barcode resolution</small> | 0 to 1 cm / 0 to 0.4 in. | 0 to 5 cm / 0 to 2 in. | 2.5 to 20 cm / 1 to 7.9 in. | 1 to 63 cm/ 0.4 to 25 in. |
| | Scanning angle | Pitch ±70° Skew ±40° | Pitch ±70° Skew ±70° | Pitch ±70° Skew ±70° | Pitch ±70° Skew ±32.5° |
| | PCS | Minimum 30% | | | |
| | Scan rate | 100 scans/second | | | 35 ± 5 scans/second |
| | Auto-sense mode | n/a | | Yes | n/a |
| | Interfaces supported | RS232, Keyboard wedge, Wand emulation (except 1000), USB HID, USB Virtual Com, IBM 4683/4694 | | | |
| | Barcodes supported | Codabar, Code 39, Code 93, Code 128, GS1 Databar (RSS), Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Pharmacodes, Plessey, Telepen, UPC/EAN/GS1-128, and more | | | |
| | Programmable features | Data editing, interface selection, symbology configuration | | | |
| | Language support | US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German | | | |
| Physical | Weight | 265 g / 9.3 oz. w/cable | 148 g / 5.2 oz. | 165 g / 5.8 oz. | 190 g / 6.7 oz. |
| | Color | Ivory | | Light grey or dark grey | |
| | Switch | Rubber switch | | Micro switch | |
| Electrical | Voltage | +5V ±5% | +5V ±5% | +5V ±10% | +5V ±5% |
| | Power Consumption <small>Standby / Scanning / Maximum</small> | 15 mA / 60 to 80 mA / 85 to 110 mA | 15 mA / 60 mA / 90 mA | 15 mA / 80 mA / 160 mA | 15 mA / 170 mA / 250 mA |
| User environment | Operating temperature | 0° to 50°C / 32° to 122°F | | | 0° to 40°C / 32° to 104°F |
| | Storage temperature | -20° to 60°C / -4° to 140°F | | | -40° to 60°C / -40° to 140°F |
| | Operating/storage humidity | Non-condensing 10% to 90% / 5% to 95% | | | |
| | Impact resistance <small>Multiple drops onto concrete</small> | 1.0 m / 3.3 ft. drops | | 2 m / 6.6 ft. drops | 1.2 m / 4 ft. drops |
| | Electrostatic discharge | Conforms to ±15 kV air discharge and ±8 kV contact discharge | | | |
| | EMC regulation | BSMI, CE, C-Tick, FCC | BSMI, CE, C-Tick, FCC, MIC | BSMI, CE, C-Tick, FCC | BSMI, CE, C-Tick, FCC, MIC |
| Configuration | Setup options include Windows®-based ScanManager software (included), by direct connection or printing out barcode settings | | | | |
| Accessories | | Includes attached cable | Detachable cable, desk/wall mount included with 1100/1200 Optional auto-sense stand for 1100 | | |
| Warranty | | 5 year | | | 1 year |

ACCESSORIES



Auto-sense Stand



1100/1105 & 1200 Holder

Can be used on tabletop or wall mounted



©2009 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.



HEADQUARTERS
CipherLab Co., Ltd.
 12F, 333 Dunhua S. Rd., Sec. 2
 Taipei, Taiwan 10669
 Tel +886 2 8647 1166
 Fax +886 2 8732 3300
 www.cipherlab.com

CipherLab China
 Suite 1305, 1065A, Jaojiabang Rd.
 Xuhui District, Shanghai,
 China 200030
 Tel +86 21 3368 0288
 Fax +86 21 3368 0286

CipherLab USA
 2552 Summit Avenue
 Plano, Texas USA 75074
 Tel +1 469 241 9779
 Toll Free 888 300 9779
 Fax +1 469 241 0697

CipherLab Central Europe
 Willicher Damm 143-145
 41066 Mönchengladbach
 Germany
 Tel +49 2161 56230 0
 Fax +49 2161 56230 22